

## Scissor lift

### ES1612E



**EXTENDEND PLATFORM**



**GRADEABILITY**



**TIGHT TURNING RADIUS**



**SAFETY BRACKET**

S.W.L.	200kg
S.W.L. on extension	113kg
Max. occupants	2
Working height	15,7 m
working height (outdoor use) - option	/
Platform floor height	13,7 m
Platform floor height (outdoor use) - option	/
Overall length	2,48 m
Overall width	1,25 m
Overall height (rails up)	2,58 m
Overall height (rails down)	2,26 m
Platform size (length/width)	2,64 m x 0,81 m
Platform extension size	0,9 m
Ground clearance (stowed)	0,1 m
Ground clearance (raised)	0,019 m
Wheelbase	2,22 m
Turning radius (inside)	0 m
Turning radius (outside)	2,65 m
Drive motors	24V/1,5kW
Lifting motors	24V/4,5kW
Travel speed (stowed)	4 km/h
Travel speed (rated)	0,8 km/h
Up\Down speed	88/60 sec
Batteries	4x12V/300Ah
Integrated charger	24V/25A
Gradeability	25%
Maximum working slope (indoor use)	1,5°/3°
Maximum working slope (outdoor use) - option	/
Tyres	ø 381x127mm
Front wheels	/
Weight (CE)	3150kg
Weight (ANSI)	/